




DRAINAGE PUMP K 3

Wastewater ▪ 1~ 230 V 50 Hz



Delivery height H m (WC)



Delivery rate Q l/min	300	250	150	0
Delivery height H m (WC)	0	2	6	9

Q l/min. at H m (Watercolumn), valid for $\rho = 1 \text{ kg/dm}^3$ and kinematic viscosity $\eta = 1 \text{ mm}^2/\text{s}$. Delivery rate and efficiency acc. to DIN 1944.

APPLICATION RANGE:

Submersible pump with electrical motor to drainage wastewater for mobile use (plug & work) featuring stainless steel motor casing.

Liquid temperature: $\leq 45^\circ\text{C}$ (up to 3 min. max. 80°C)
 Liquid density: $\leq 1,1 \text{ kg/dm}^3$
 Allowed pH range: 5-8

SPECIFICATIONS:

Electric motor: 1 ~ 230 V A.C.
Power P_1 / P_2 : 650 / 380 W
Rated current: 3,1 A
Gross weight: 5,8 kg
Dimensions: $\varnothing 175 \times \text{H } 282 \text{ mm}$
Discharge: G 1 ¼ " female thread
Solids passage: $\varnothing 10 \text{ mm}$
Connecting cable: H 07 RN-F 3G1,0 (10 m)
Connection plug: Schuko CEE 7/4 (type F), IP 44

MATERIALS:

Motor casing: Stainless steel 1.4301
Motor shaft: Stainless steel 1.4122
Screws: Stainless steel A 2
Outer casing: PP fibre-glass reinforced 30 %
Impeller: Polyacetat POM
O-rings: Perbunan NBR
Shaft seal: Triple shaft, Perbunan NBR

FEATURES:

- **standard flat suction appliance to aspirate even lowest water levels, ready to wipe.**
- available with voltage 115 V
- maintenance-free
- dry-running safe
- electric motor with thermal overload protection
- optional with FPM (Viton) o-rings for lightly contaminated water
- optional with hosepipe „Geka“- coupling or C-STORZ coupling



powerful
robust
reliable

www.mast-pumpen.de

MAST PUMPEN GmbH
 Pump factory
 Mörikestr. 1
 D-73773 Aichwald GERMANY
 Tel.: + 49 711/936704-0 Fax: -30
 info@mast-pumpen.de